



2.8 Dati tecnici

2.8 Technical data

2.8 Technische Daten

T	n ₁ = 1400			TC - TF				TA	
	in	ir	n ₂ rpm	T ₂ Nm	P ₁ kW	FS'	IEC	T _{2M} Nm	P kW
140B	7*	6.88	203	983	22	1.4	TC-TF	1350	30.2
	10	10.25	137	1461	22	1.3		1850	27.9
	12.5	13.05	107	1860	22	1.1		2050	24.3
	16	15.63	90	1874	18.5	1.2		2200	21.7
	20	19.64	71	2354	18.5	1.0		2400	18.9
	25	24.99	56	2429	15	1.0		2540	15.7
	31.5	29.95	47	2135	11	1.1		2300	11.9
	40	38.73	36	1882	7.5	1.2		2210	8.8
	50	50.18	28	1789	5.5	1.2		2120	6.5
	63	60.13	23	2143	5.5	1.1		2350	6.0
80	77.76	18	2016	4	1.1	2250	4.5		
125C	50	52.18	27	2483	7.5	1.1	TC-TF	2650	8.0
	63	62.53	22	2182	5.5	1.3		2760	7.0
	80	79.58	18	2777	5.5	1.0		2880	5.7
	100	99.97	14	2537	4	1.2		3000	4.7
	125	119.78	12	2280	3	1.3		3000	4.0
	160	152.45	9	2128	2.2	1.3		2720	2.8
	200	182.67	8	2549	2.2	1.1		2800	2.4
	250	240.51	6	2746	1.8	1.1		3050	2.0
	315	306.11	5	2913	1.5	1.0		2960	1.5
	400	366.78	4	2560	1.1	1.1		2800	1.2
180B	10	10.25	137	1993	30	2.0	TC-TF	3900	58.7
	12.5	13.05	107	2536	30	1.7		4300	50.9
	16	15.63	90	3039	30	1.5		4500	44.4
	20	19.64	71	3818	30	1.3		5100	40.1
	25	24.99	56	4859	30	1.1		5230	32.3
	31.5	29.95	47	4269	22	1.1		4680	24.1
	40	38.73	36	3764	15	1.1		4300	17.1
	50	50.18	28	3577	11	1.2		4300	13.2
	63	60.13	23	4286	11	1.1		4780	12.3
	80	77.76	18	3779	7.5	1.2		4380	8.7
160C	50	52.18	27	4966	15	1.0	TC-TF	5130	15.5
	63	62.53	22	4363	11	1.2		5350	13.5
	80	79.58	18	4644	9.2	1.2		5570	11.0
	100	99.97	14	4756	7.5	1.2		5800	9.2
	125	119.78	12	5699	7.5	1.0		5800	7.6
	160	152.45	9	5319	5.5	1.0		5470	5.7
	200	182.67	8	4635	4	1.2		5600	4.8
	250	240.51	6	4577	3	1.3		5890	3.3
	315	306.11	5	5826	3	1.0		5920	3.0
	400	366.78	4	5119	2.2	1.1		5600	2.4
500	474.35	3	4514	1.5	1.2	5280	1.8		
630	613.46	2	4281	1.1	1.2	4960	1.3		

T	n ₁ = 1400			TC - TF				TA	
	in	ir	n ₂ rpm	T ₂ Nm	P ₁ kW	FS'	IEC	T _{2M} Nm	P kW
200B	8	8.14	172	1582	30	3.2	TC-TF	5000	94.8
	10	10.43	134	2028	30	2.7		5500	81.4
	12.5	12.60	111	2449	30	2.4		6000	73.5
	16	15.63	90	3039	30	2.1		6500	64.2
	20	17.65	79	3432	30	2.1		7100	62.1
	25	24.14	58	4692	30	1.5		7150	45.7
	31.5	29.95	47	5822	30	1.2		7250	37.4
	40	33.82	41	6575	30	1.1		7300	33.3
	50	47.93	29	6833	22	1.1		7400	23.8
	63	54.13	26	6489	18.5	1.1		7400	21.1
180C	50	53.11	26	6234	18.5	1.2	TC-TF	7240	21.5
	63	63.64	22	6056	15	1.2		7280	18.0
	80	76.85	18	7313	15	1.0		7420	15.2
	100	99.39	14	6936	11	1.1		7500	11.9
	125	122.88	11	7172	9.2	1.0		7500	9.6
	160	147.23	10	7005	7.5	1.1		7550	8.1
	200	190.41	7	6644	5.5	1.1		7600	6.3
	250	246.73	6	6261	4	1.2		7650	4.9
	315	295.63	5	7502	4	1.0		7700	4.1
	400	382.33	4	7276	3	1.1		7950	3.3
225B	8	8.44	166	2461	45	3.0	TF	7500	137.1
	10	10.13	138	2955	45	2.8		8300	126.4
	12.5	12.45	112	3630	45	2.5		9100	112.8
	16	15.93	88	4644	45	2.2		10000	96.9
	20	19.13	73	5577	45	1.9		10700	86.3
	25	23.49	60	6850	45	1.6		11000	72.3
200C	31.5	30.29	46	8832	45	1.3	TC-TF	11100	56.6
	40	37.09	38	8892	37	1.2		10800	44.9
	40	42.62	33	8110	30	1.3		10900	40.3
	50	51.18	27	9740	30	1.1		11000	33.9
	63	62.86	22	8772	22	1.3		11350	28.5
	80	76.97	18	10742	22	1.0		11050	22.6
	100	98.04	14	9330	15	1.2		11200	18.0
	125	120.41	12	11459	15	1.0		11500	15.1
	160	147.45	9	10290	11	1.1		11200	12.0
	200	196.87	7	9367	7.5	1.2		11400	9.1
250	241.79	6	11504	7.5	1.0	11700	7.6		
315	296.07	5	10330	5.5	1.1	11850	6.3		

Flange quadrate / Square flanges / Viereckige Flansche

* Rapporto speciale / Special ratio / Sonderverhältnisse